

BY-LP42T

Thermal Transfer Label printer

LP42T è una stampante di etichette professionale con larghezza di stampa da 110 mm.

Può stampare in modalità Termica diretta oppure a Trasferimento.

Include drivers per Windows, ha alte prestazioni e monta 2 interfacce per consentire una facile integrazione nelle più svariate applicazioni.

RS232, Ethernet (opz), USB permettono di usare la stampante connessa ai moderni sistemi ormai in uso in molteplici attività, quali spedizioni produzione, magazzino e tantissime altre...

Il sensore di gap o di tacca nera, completano la dotazione facendone una stampante dal rapporto prezzo / prestazioni imbattibile.




Caratteristiche

Item	Parameters	
Print	Print method	Thermal/thermal transfer
	Resolution	203 DPI
	Print width	Max.104mm
	Print speed	Max.100mm/s
	Memory	SDRAM:64MB, FLASH:4MB(standard), 8MB(optional)
Interface	Standard:	USB(on-board)
	Optional:	Parallel, Serial, Ethernet, WLAN(Wi-Fi)
Barcode	1D Barcode	Code 3 of 9, UPCA, UPCE, Interleaved 2 of 5, code 128, EAN13, EAN8, HBIC (39 code with checkout), Codabar, industry CODE25, storage and transportation Code, UPC2, UPC5, Code 93, Postnet 25 (China), UCC/EAN, matrix 25, POSTNET code, etc.
	2D Barcode	PDF417, MAXICODE, QR code etc.
Paper	Paper type	Continuous paper, Marked paper, Label paper
	Paper width	Max.118mm
	Paper roll ID	25mm/38mm
	Paper roll OD	Max.127mm
Ribbon	Ribbon length	Max.91m
	Ribbon ID	12.5mm
Power supply	Input	100~240V AC,50~60Hz
	Output	24V DC, 1.5A
Environment	Operation condition	5~45°C□20~90%RH□40°C□
	Storage condition	-40~60°C□20~93% RH□40°C□
Physics Spec.	Dimensions	218(W)×278(D)×185(H)mm
	Weight	Approx.2.3Kg

YES We Scan!

www.barcodeyes.com



Quality hardware for BARCODE