


BY-80 II

Multi Interface POS Printer

YES We Scan!

www.barcodeyes.com



BY-80II è una stampante POS professionale con larghezza di stampa da 80 mm.

Termica diretta e dotata di driver per Windows, ha alte prestazioni e 3 interfacce per consentire una facile integrazione nelle più svariate applicazioni per il punto vendita.

RS232, Ethernet, USB permettono di usare la stampante connessa ai moderni sistemi ormai in uso in molteplici attività, quali ristorazione, wellness, sale scommesse, produzione... e tantissime altre...

Il sensore di tacca nera, e la stampa dei barcode completano la dotazione facendone una stampante dal rapporto prezzo / prestazioni imbattibile.



Caratteristiche

Print Speed	230mm /Second (63 Lines/Second)
Cutting Method	Auto-Cutter -Selectable Full or Partial Cut
Resolution	180 DPI x 180 DPI
Char Per line	Font A: 42 (72mm) / 33 (58mm) Font B: 56 (72mm) / 45 (58mm)
Characters Size	Font A: 12 x 24; Font B: 9 x 17
Paper Supply	Drop and Print
Reliability MTBF	360,000 Hours
MCCBF	60,000,000 Lines
Character Set	Alphanumeric: 95, International: 13, Code Pages 56
Bar Code	UPC-A, UPC-E, EAN8, EAN13, Code 39, Code 93, Code 128, ITF PDF 417, CODABAR, QR Code, MaxiCode, GSI
Compatibility	ESC/POS

Interface	Serial + USB + Ethernet
Drivers	Windows 8.1 32 and 64-bit/ Windows 8 32 and 64-bit/ Windows 7 32 and 64-bit/ Server 2012 32 and 64-bit/ Server 2008 32 and 64-bit/ Server 2003 32 and 64-bit/ 2000 Server 32-bit/2000 Server Professional/ Windows Vista 32 and 64-bit / Windows XP Professional 32 and 64-bit / Windows POSReady 2009 32-bit/ Linux CUPS / JavaPOS / OPOS
Buzzer	Internal (Standard)
Drawer Port	Supports Two 24VDC Drawers w/ Compulsion
Data Buffer	Receive Buffer RAM: 64 KB RAM, Bitmap: 128 KB, Flash Bitmap: 512 KB
Power Supply	AC 100 ~ 240 V, 50/60 HZ Adapter Included
Dim & Weight	145(mm)W x 141(mm)H x 195(mm)D 1.45 Kg

Quality hardware for BARCODE