



E1600

**Compact Omnidirectional
Laser scanner**

E-1600 è un potente lettore laser omnidirezionale, compatto e con elevato regime di scansioni per secondo.

La eccellente conformazione del pattern Laser con 20 linee incrociate consente una capacità di lettura e decodifica particolarmente aggressiva.

Il piccolo contenitore e la testa orientabile permettono un facile posizionamento sul banco senza dover ingombrare l'area di lavoro.



Specifiche

Fisiche

Profondità: 114 mm
Larghezza: 156 mm
Altezza: 114 mm
Peso: 290 g. (senza cavo)

Elettriche

Alimentazione: 5 V. DC
Assorbimento: 220 mAh max.

Interfaccia

USB, RS232, Emulazione di tastiera

Caratteristiche

Sorgente di luce: Diodo laser 650 nm.
Prof. di campo: 0 to 300 mm. (dip. da Risoluzione)
Scansioni: 1650 Scan/s. (5 direzioni 20 linee laser)
Risoluzione: 4 mil
Contrasto: 30% @ UPC / EAN 100%



Simbologie

UPC/EAN/JAN,UPC-A & UPC-E,EAN-8 & EAN-13, JAN-8
JAN-13, ISBN/ISSN, Code 39 (with full ASCII), Codabar
(NW7), Code 128 & EAN 128,Code 93,Interleaved 2 of 5 (ITF)
Addendum 2 of 5, IATA Code,MSI/Plessey, China Postal Code
Code 32 (Italian Pharmacode),RSS 14,RSS Limited, RSS Expanded

Operative

Cavo: 200 Cm. cavo dritto
Connettore: RJ45 to USB / DSUB / MiniDin
Indicatori: 2 colours Led, buzzer

Ambientali

Temperatura operativa: 0° to 40°
Temperatura conservazione: -20° to 60°
Umidità: 5% to 90% RH (non condensata)

YES We Scan!

www.barcodeyes.com



Quality hardware for BARCODE

